

## **FB 505**

## REVERSIBLE VIBRATORY PLATE





- The Swepac FB 505 is a heavyweight, and yet compact, diesel-powered machine with high compaction capacity. Despite its weight, it is well balanced and easy to maneuver.
- The FB 505 has a belt-driven transmission and a fully variable speed control.
- Comes with either joystick or handle control.
- The Hardox® base plate ensures a long service life.
- The machine is well protected and has easily accessible service points.
- Very easy to refuel as the fuel cap is located outside the protection cover.
- The robust and galvanized protection frame effectively protects against external damage and is equipped with a strong and powerful lifting hook
- The ergonomics are top class with a de-vibrated control handle (HAV < 2,5 m/s²) having both directional and speed control.

## For compaction of sand, gravel and rockfill.

All our machine models are versatile and easy to operate. They are also durable and reliable, meaning lower operating and maintenance costs.

TECHNICAL DATA – <b>SWEPAC FB 505</b>	
Weight, net	440 kg
Base plate, width x length	700 x 1080 mm
Height, max / min	1235 / 1050 mm
Length, max / min	1830 / 1180 mm
Engine	Hatz 1B50
Fuel tank capacity	5 liter
Fuel	Diesel
Engine output, max	7,9 kW (10,1 hp)
Battery capacity	44 Ah
Generator capacity	180 W (15A)
Centrifugal force	66 kN
Frequency	72 Hz
Working speed	0 – ca 25 m/min

Hand/arm vibrations HAV according to ISO 5349 on gravel surface	< 2,5 m/s <sup>2</sup>
GaranteradGuaranteed sound-power level, LwA	108 dB(A)
Sound pressure level (at operator's ear), OP	93 dB(A)

PART NUMBER	
309100	FB 505 with handle control
309150	FB 505 with joystick control

OPTIONS AND ACCESSORIES	
Handle heating for joystick controlled machine	
Compaction indicator	
Hour meter	

B505 2025-02 GF